



# OAK CADENCE

## PRODUCT DETAILS

<b>Article Number</b>	13103AEK1PKW185
<b>EAN Code</b>	7393969107358
<b>Surface Treatment</b>	Matte finish
<b>Refining Treatment</b>	Microbeveled 4-sided, Brushed
<b>Dimensions</b>	73 1/4 x 5 x 1/2"
<b>Weight per Package</b>	28 lbs
<b>Area per Package</b>	17.8 sqft
<b>Area per pallet (m<sup>2</sup>)</b>	1120.3 sqft
<b>Package info</b>	Packages may contain start and stop boards.

## COLOR CHANGE

Stained product - noticeable color change over time.

## FACTS

<b>Wood Species</b>	White Oak
<b>Design</b>	1-strip
<b>Grading</b>	Calm
<b>Range</b>	Kährs Avanti
<b>Collection</b>	Canvas Collection
<b>Resandable</b>	2 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes 25 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	1/8"
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness</b>	1/2"
<b>Surface Color</b>	Dark brown
<b>Installation method</b>	Floating, Glue-Down

## TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,08 W/mK
<b>Thermal Resistance R-Value</b>	.15 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	



**Descriptions & Imagery**

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*